

36 KINGSTHORPE ROAD
HOVE
BN3 5HR
Tel 01273 260 260
Fax 01273 260 270
E-mail artbox@lawrence.co.uk

GOLDEN MSA Varnish and GOLDEN MSA Top-coat with UVLS (Gloss, Matte or Satin Finish)

SECTION 1. COMPANY AND PRODUCT IDENTIFICATION

RECOMMENDED USE: Final protective coating for Fine Art.

COMPANY DETAILS: Golden Artist Colors, Inc.
188 Bell Road
New Berlin, NY 13411
(607) 847—6154
gavett@goldenpaints.com

SECTION 2. HAZARD IDENTIFICATION

| | | |
|-------------------|--|-----------------------------|
| PHYSICAL HAZARDS: | Flammable liquids | Category 3 |
| | Skin corrosion/irritation | Category 2 |
| | Sensitization, skin | Category 1 |
| | Carcinogenicity | Category 2 |
| | Specific target organ toxicity, single exposure | Category 3 narcotic effects |
| | Specific target organ toxicity, repeated exposure | Category 2 (Kidney) |

OSHA HAZARDS: Not classified.

LABEL ELEMENTS:



SIGNAL WORD: Warning

HAZARD STATEMENT: May cause an allergic skin reaction. Suspected of causing cancer. May cause damage to organs (Kidney) through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS

PREVENTION: Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces.—No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/ eye and face protection. Do not breathe mist/vapours/spray. Contaminated work clothing must not be allowed out of the work place. Do not eat, drink or smoke when using the product. Wash thoroughly after handling.

RESPONSE: If exposed or concerned: Get medical attention/advice. If on skin or hair: take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. If inhaled: remove person to fresh air and keep comfortable for breathing. Call a poison centre/doctor if you feel unwell. In case of fire: use foam, carbon dioxide, dry powder or water fog for extinction.

STORAGE: Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

DISPOSAL: Dispose of contents/container in accordance with local/regional/national/international regulations.

DISPOSAL: Dispose of contents/container in accordance with local/regional/national/international regulations.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC): Static accumulating flammable liquids

| | | |
|------------------------|---|------------|
| ENVIRONMENTAL HAZARDS: | Hazardous to the aquatic environment, acute hazard | Category 2 |
| | Hazardous to the aquatic environment, long-term hazard | Category 2 |

HAZARD STATEMENT: Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENT

PREVENTION: Avoid release to the environment.

RESPONSE: Collect spillage

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

| CHEMICAL NAME | CAS NUMBER | % |
|--|-------------|--------|
| Stoddard solvent | 8052-41-3 | 50-<60 |
| Silicon dioxide | 112945-52-5 | 5-<10 |
| Solvent naphtha (petroleum), heavy arom. | 64742-94-5 | 3-<5 |
| Bis (1,2,2,6,6-pentam ethyl-4-piperidyl) sebacate | 41556-26-7 | 0.1-<1 |
| Naphthalene | 91-20-3 | 0.1-<1 |

COMPOSITION COMMENTS: All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

SECTION 4. FIRST-AID MEASURES

INHALATION: Move to fresh air. If breathing is difficult, give oxygen. Get medical attention.

SKIN CONTACT: Remove contaminated clothing immediately and wash skin with soap and water. Continue to rinse for at least 15 minutes. In case of eczema or other skin disorders: seek medical attention and take along this MSDS.

EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do. Get medical attention if irritation develops and persists.

INGESTION: Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Only induce vomiting at the instruction of medical personnel. Get medical attention if any discomfort continues.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

Overexposure to mist/vapours of this product may cause headache, dizziness, nausea, and respiratory tract irritation. Symptoms include itching, burning, redness and tearing. Vapours may cause drowsiness and dizziness. Defats the skin.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Treat symptomatically. The effects might be delayed.

GENERAL INFORMATION: Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

SECTION 5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Foam, Carbon Dioxide (CO₂), Dry chemical. Powder.

UNSUITABLE EXTINGUISHING MEDIA: Do not use water jet as an extinguisher, as this will spread the fire.

SPECIFIC HAZARDS ARISING FROM CHEMICAL:

Thermal decomposition may produce smoke, oxides of carbon and lower molecular weight organic compounds whose composition has not been characterized.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIREFIGHTING:

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

FIRE-FIGHTING EQUIPMENT/INSTRUCTIONS:

Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Cool containers with flooding quantities of water until well after fire is out.

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS. PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Avoid inhalation or vapours and spray mist and contact with skin and eyes. Wear suitable protective clothing. For personal protection, see Section 8.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:

Remove sources of ignition. Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Collect spillage. Absorb spillage with non-combustible, absorbent material.

ENVIRONMENTAL PRECAUTIONS: Do not discharge into drains, water courses or onto the ground.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING: Use only in well-ventilated areas. Avoid inhalation of vapours/spray and contact with skin and eyes. Wear appropriate personal protective equipment. The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures. Do not smoke and do not spray near a naked flame or other sources of ignition. Read label before use. Do not smoke and do not spray near an open flame or other source of ignition.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:

Keep away from heat, sparks and open flame. Keep in cool, well-ventilated place. Keep out of reach of children.

SECTION 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMITS

US. OSHA TABLE Z-1 LIMITS FOR AIR CONTAMINANTS (29 CFR 1910.1000)

| COMPONENTS | CAS NUMBER | TYPE | VALUE | |
|------------------|------------|------|------------------------|---------|
| Naphthalene | 91-20-3 | PEL | 50 mg/m ³ | 10 ppm |
| Stoddard solvent | 8052-41-3 | PEL | 2900 mg/m ³ | 500 ppm |

US. OSHA TABLE Z-3 (29 CFR 1910.1000)

| COMPONENT | CAS NUMBER | TYPE | VALUE | |
|-----------------|-------------|------|-----------------------|----------|
| Silicon dioxide | 112945-52-5 | TWA | 0.8 mg/m ³ | 20 mppcf |

US. ACGIH THRESHOLD LIMIT VALUES

| COMPONENTS | CAS NUMBER | TYPE | VALUE | |
|------------------|------------|------|---------|--|
| Naphthalene | 91-20-3 | STEL | 15 ppm | |
| | | TWA | 10 ppm | |
| Stoddard solvent | 8052-41-3 | TWA | 100 ppm | |

US NIOSH POCKET GUIDE TO CHEMICAL HAZARDS: CEILING LIMIT VALUE AND TIME PERIOD (IF SPECIFIED)

| COMPONENTS | CAS NUMBER | TYPE | VALUE | |
|------------------|------------|---------|------------------------|--|
| Stoddard solvent | 8052-41-3 | Ceiling | 1800 mg/m ³ | |

US NIOSH POCKET GUIDE TO CHEMICAL HAZARDS: RECOMMENDED EXPOSURE LIMIT (REL)

| COMPONENT | CAS NUMBER | TYPE | VALUE | |
|------------------|-------------|------|-----------------------|--------|
| Naphthalene | 91-20-3 | TWA | 50 mg/m ² | 10 ppm |
| Silicon dioxide | 112945-52-5 | TWA | 6 mg/m ³ | |
| Stoddard solvent | 8052-41-3 | TWA | 350 mg/m ³ | |

US NIOSH POCKET GUIDE TO CHEMICAL HAZARDS: SHORT TERM EXPOSURE LIMIT (STEL)

| COMPONENTS | CAS NUMBER | TYPE | VALUE | |
|-------------|------------|------|----------------------|--------|
| Naphthalene | 91-20-3 | STEL | 75 mg/m ³ | 15 ppm |

BIOLOGICAL LIMIT VALUES: No biological exposure limits noted for the ingredients.

EXPOSURE GUIDELINES:

US ACGIH THRESHOLD LIMIT VALUES: SKIN DESIGNATION

Naphthalene (CAS 91-20-3) Can be absorbed through the skin.

APPROPRIATE ENGINEERING CONTROLS: Use explosion-proof ventilation equipment. Provide adequate ventilation.

Observe Occupational Exposure Limits and minimize the risk of inhalation of spray. Provide easy access to water supply or an emergency shower.

INDIVIDUAL PROTECTION MEASURES:

EYE/FACE PROTECTION: Wear approved safety glasses or goggles.

SKIN PROTECTION:

HAND PROTECTION: Solvent-resistant gloves. Be aware that the liquid may penetrate the gloves.

Frequent change is advised. Suitable gloves can be recommended by glove supplier.

OTHER: Wear appropriate chemical resistant clothing to prevent any possibility of skin contact.

RESPIRATORY PROTECTION: Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure.

Consult with respirator manufacturer to determine selection, use and limitations. Use positive pressure, air-supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded.

Follow respirator protection program requirements (OSHA 1910. 134 and ANSI Z88.2) for all respirator use

THERMAL HAZARDS: Wear appropriate thermal protective clothing, when necessary.

GENERAL HYGIENE CONSIDERATIONS: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Private clothes and working clothes should be kept separately. Personal protective equipment should not be worn during lunch breaks.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Clear, viscous liquid

ODOUR: Mineral spirits

ODOUR THRESHOLD: Not available

pH: Not applicable

MELTING/FREEZING RANGE: Not available

BOILING RANGE: Not available

FLASH POINT: 105.8 °F (41.0°C) Tag Closed Cup

EVAPORATION RATE: Not applicable

FLAMMABILITY: Not applicable

VAPOUR PRESSURE: Not available

VAPOUR DENSITY: Not available

RELATIVE DENSITY: 0.91

SOLUBILITY: Not available

PARTITION COEFFICIENT: Not available

AUTO-IGNITION TEMP.: Not available

DECOMPOSITION TEMP.: Not available

VISCOSITY: 2000—4500 c P

VOC (WEIGHT %): 56.5 % w/w

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY: Stable at normal conditions

CHEMICAL STABILITY: Material is stable under normal conditions

POSSIBILITY OF HAZARDOUS REACTIONS: Will not occur

CONDITIONS TO AVOID: Heat, sparks, flames, elevated temperatures. Contact with incompatible materials.

INCOMPATIBLE MATERIALS: Strong acids. Strong oxidising agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON LIKELY ROUTES OF EXPOSURE

INGESTION: Ingestion may cause irritation and malaise.

INHALATION: Vapours and spray mist may irritate throat and respiratory system and cause coughing. May cause nervous system effects.
SKIN CONTACT: Causes skin irritation.
EYE CONTACT: May cause eye irritation.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS:

Overexposure to mist/vapours of this product may cause headache, dizziness, nausea, and respiratory tract irritation. Symptoms include itching, burning, redness and tearing. Defats the skin.

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY: May cause central nervous system effects.

| COMPONENTS | SPECIES | TEST RESULTS |
|---|---------|------------------|
| Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (CAS 41556-26-7) | | |
| ACUTE | | |
| Oral | | |
| LD50 | Rat | 2369– 4247 mg/kg |

Naphthalene (CAS 91-20-3)

| | | |
|--------|--------|-----------|
| ACUTE | | |
| Dermal | | |
| LD 50 | Rabbit | > 2 g/kg |
| Oral | | |
| LD50 | Rat | 490 mg/kg |

Solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)

| | | |
|------------|--------|-------------------------|
| ACUTE | | |
| Dermal | | |
| LD 50 | Rabbit | >3160 mg/kg |
| Inhalation | | |
| LC 50 | Rat | > 590 mg/m ³ |
| Oral | | |
| LD 50 | Rat | 7050 mg/kg |

Stoddard solvent (CAS 8052-41-3)

| | | |
|------------|--------|---------------------|
| ACUTE | | |
| Dermal | | |
| LD 50 | Rabbit | > 2000 mg/kg |
| Inhalation | | |
| LC 50 | Rat | > 5.2 mg/l, 4 hours |
| Oral | | |
| LD 50 | Rat | > 5000 mg/kg |

SKIN CORROSION/IRRITATION: Causes skin irritation
SERIOUS EYE DAMAGE/IRRITATION: May cause eye irritation
RESPIRATORY SENSITIZATION: Not classified
SKIN SENSITIZATION: The product contains a small amount of sensitizing substance which may provoke an allergic reaction among sensitive individuals.
GERM CELL MUTAGENICITY: Knowledge about mutagenicity is incomplete
CARCINOGENICITY: Suspected of causing cancer

IARC MONOGRAPHS. OVERALL EVALUATION OF CARCINOGENICITY

| | |
|------------------------------------|--|
| Naphthalene (CAS 91-20-3) | 2B Possibly carcinogenic to humans |
| Silicon dioxide (CAS 112945 –52-5) | 3 Not classifiable as to carcinogenicity to humans |

NTP REPORT ON CARCINOGENS

| | |
|---------------------------|---|
| Naphthalene (CAS 91-20-3) | Reasonably Anticipated to be a Human Carcinogen |
|---------------------------|---|

REPRODUCTIVE TOXICITY: Knowledge about reproductive effects is incomplete.

SPECIFIC TARGET ORGAN TOXICITY—SINGLE EXPOSURE: May cause drowsiness and dizziness.

SPECIFIC TARGET ORGAN TOXICITY—REPEATED EXPOSURE: May cause damage to organs (Kidney) through prolonged or repeated exposure.

ASPIRATION HAZARD: Not classified

CHRONIC EFFECTS: Prolonged or repeated contact with skin may cause redness, itching irritation, eczema/chapping and oil acne. Organic solvents may be absorbed into the body by inhalation and cause permanent damage to the nervous system, including the brain. May cause damage to the kidneys.

SECTION 12. ECOLOGICAL INFORMATION

ECOTOXICITY: Toxic to aquatic life with long lasting effects.

| COMPONENTS | SPECIES | TEST RESULTS |
|---|---|--------------------------|
| Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (CAS 41556-26-7) | | |
| AQUATIC | | |
| Fish | LC 50 Bluegill (<i>Lepomis macrochirus</i>) | 1 mg/l, 96 hours |
| Naphthalene (CAS 91-20-3) | | |
| AQUATIC | | |
| Crustacea | EC 50 Water flea (<i>Daphnia magna</i>) | 1.09—3.4 mg/l, 48 hours |
| Fish | LC 50 Pink salmon (<i>Oncorhynchus gorbuscha</i>) | 1.11—1.68 mg/l, 96 hours |
| Solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5) | | |
| AQUATIC | | |
| Fish | LC 50 Fathead minnow (<i>Pimephales promelas</i>) | 45 mg/l. 96 hours |

PERSISTENCE AND DEGRADABILITY: The product is not expected to be readily biodegradable.

BIOACCUMULATIVE POTENTIAL

PARTITION COEFFICIENT N-OCTANOL / WATER (log Kow)

Stoddard solvent (CAS 8052-41-3) 3.16—7.15

MOBILITY IN SOIL: No data available

MOBILITY IN GENERAL: The product contains organic solvents which will evaporate easily from all surfaces.

OTHER ADVERSE EFFECTS: The product contains volatile organic compounds which have a photochemical ozone creation potential.

SECTION 13. DISPOSAL CONSIDERATIONS

DISPOSAL INSTRUCTIONS: Contract with a disposal operator licensed by the Law on Disposal and Cleaning. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Must be incinerated in a suitable incineration plant holding a permit delivered by the competent authorities. Do not discharge into drains, water courses or onto the ground. This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria of hazardous waste. Dispose of contents/container in accordance with local/regional/international regulations. When your own wastewater treatment plant is not available, collect entire waste and then charge to a licensed industrial waste management professional with manifests for industrial waste.

HAZARDOUS WASTE CODE: D001: Waste Flammable material with a flash point < 140 F

US RCRA HAZARDOUS WASTE U LIST: REFERENCE

Naphthalene (CAS 91-20-3) U165

WASTE FROM RESIDUES/ UNUSED PRODUCTS: Dispose in accordance with all applicable regulations.

CONTAMINATED PACKAGING: Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

DOT

UN NUMBER: UN1263
UN PROPER SHIPPING NAME: Paint
TRANSPORT HAZARD CLASS: 3

DOT

UN NUMBER: UN1263
UN PROPER SHIPPING NAME: Paint
TRANSPORT HAZARD CLASS: 3
SUBSIDIARY CLASS: -
PACKING GROUP: III
ENVIRONMENTAL HAZARDS: Marine Pollutant: Yes

SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling

SPECIAL PROVISIONS: B1, B52, IB3, T2, TP1
PACKING EXCEPTIONS: 150
PACKING NON BULK: 173
PACKING BULK: 242

IATA

UN NUMBER: UN1263
UN PROPER SHIPPING NAME: Paint
TRANSPORT HAZARD CLASS: 3
SUBSIDIARY CLASS: - III
PACKING GROUP: Yes
ENVIRONMENTAL HAZARDS: 3
LABELS REQUIRED: 3L
ERG CODE

SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling

IMDG

UN NUMBER: UN1263
UN PROPER SHIPPING NAME: Paint
TRANSPORT HAZARD CLASS: 3
SUBSIDIARY CLASS: -
PACKING GROUP: III
ENVIRONMENTAL HAZARDS: Marine Pollutant: Yes
LABELS REQUIRED: 3
EmS: F-E, S-E

SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling

TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE:

This substance/mixture is not intended to be transported in bulk.

SECTION 15. REGULATORY INFORMATION

US FEDERAL REGULATIONS: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA SECTION 12(B) EXPORT NOTIFICATION (40 CFR 707, SUBPT. D): Not regulated

US. OSHA SPECIFICALLY REGULATED SUBSTANCES (29 CFR 1910. 1001-1050): Not listed

CERCLA HAZARDOUS SUBSTANCE LIST (40 CFR 302.4):

Naphthalene (CAS 91-20-3) LISTED

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA)

HAZARD CATEGORIES: Immediate Hazard - Yes
Delayed Hazard- Yes
Fire Hazard - Yes
Pressure Hazard- No
Reactivity Hazard- No

SARA 302 EXTREMELY HAZARDOUS SUBSTANCE: No

SARA 311/312 HAZARDOUS CHEMICAL: Yes

SARA 313 (TRI REPORTING):

| CHEMICAL NAME | CAS NUMBER | % BY WT. |
|---------------|-------------|----------|
| Naphthalene | CAS 91-20-3 | 0.1—< 1 |

CLEAN AIR ACT (CAA) SECTION 112 HAZARDOUS AIR POLLUTANTS (HAPs) LIST: Naphthalene (CAS 91-20-3)

CLEAN AIR ACT (CAA) SECTION 112R ACCIDENTAL RELEASE PREVENTION (40 CFR 68.130): Not regulated

US STATE REGULATIONS: WARNING: This product contains chemicals known to the State of California to cause cancer.

US. MASSACHUSETTS RTK—SUBSTANCE LIST:

Naphthalene (CAS 91-20-3)
Silicon dioxide (CAS 112945-52-5)
Stoddard solvent (CAS 8052-41-3)

US. NEW JERSEY WORKER AND COMMUNITY RIGHT-TO-KNOW ACT

Naphthalene (CAS 91-20-3) 500lbs

US. PENNSYLVANIA RTK—HAZARDOUS SUBSTANCES

Naphthalene (CAS 91-20-3)
Silicon dioxide (CAS 112945-52-5)
Stoddard solvent (CAS 8052-41-3)
Solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)

US. RHODE ISLAND RTK

Naphthalene (CAS 91-20-3)

US. CALIFORNIA PROPOSITION 65

US—CALIFORNIA PROPOSITION 65—CARCINOGENS & REPRODUCTIVE TOXICITY (CRT): LISTED SUBSTANCE

Naphthalene (CAS 91-20-3)


INTERNATIONAL INVENTORIES

| COUNTRY OR REGION | INVENTORY NAME | ON INVENTORY (YES/NO)* |
|-----------------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
| Canada | Domestic Substance List (DSL) | Yes |
| Canada | Non-Domestic Substance List (NDSL) | No |
| China | Inventory of Existing Chemical Substance in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | Yes |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| United States & Puerto Rico | Toxic Substance Control Act (TSCA) Inventory | Yes |

* A 'Yes' indicates this product complies with the inventory requirements administered by the local governing country. A 'No' indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country.

SECTION 16. OTHER INFORMATION

NFPA RATINGS:



LIST OF ABBREVIATIONS: LD 50: Lethal Dose, 50%
 LC 50: Lethal Concentration, 50%
 EC 50: Effective Concentration, 50%

DISCLAIMER: The information on this sheet was written based on the best knowledge and experience currently available.